



Stripping, Sanding, Carpet Care, Resurfacing

The HAWK Osprey is the all surface restoration machine for vinyl, stone, wood, concrete, ceramic tile and carpet. A 45 PSI solution pump, 4.5 gallon solution tank and the adjustable 60 degree spray nozzle control the precise amount of cleaning solution to the floor.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 12-3 SJTOW power cord with molded plug

Drive System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler
- Gears drive brushes and pads at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece chrome, heavy-duty steel handle with variable position lock and vinyl grips
- 13", 15", 17" and 20" steel brush covers with full wraparound bumper
- Private branding - 7 color plus chrome brush covers
- The 45 PSI solution pump is powered by the machine motor and controlled by the conveniently mounted handle switch
- A handle-mounted 4.5 gallon solution tank feeds the pump
- The solution spray valve on the pump delivers liquids to the floor at 0.25 gallon per minute
- Dual steel operating triggers. Negative pressure on/off switch.
- Thumb-operated safety switch
- Includes premium double hook pad driver and splash guard
- 1" x 5" non-marking ball bearing wheels

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model #	HP1513-180OSPNEY	HP1515-180OSPNEY	HP1517-180OSPNEY	HP1520-180OSPNEY
Part Number	F0013-SP	F0006-SP	F0009-SP	F0012-SP
Machine Size	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	7.2 Amp	7.5 Amp	7.9 Amp	8.4 Amp
Machine Wt.	123 lbs.	127 lbs.	133 lbs.	135 lbs.

w/Pump & Solution Tank

All Sizes

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power	115-230V, 60 Hz power
Power Cord	50 ft. 12-3 SJTOW industrial power cord w/molded plug
Drive System	Triple-planetary XHD 11:1 helical-cut industrial gears
Solution Pump	45 psi solution pump mounted on motor
dB Rating	66 dB - Meets GS42 standard

Subject to Change Without Notice



Welded Steel Frame, Handle & Brush Covers



45 PSI Switch-Activated Pump and Solution Tank



Includes Premium Double Hook Pad Driver w/ Riser



7 Stock Colors Plus Chrome



HAWK HD Accessories



20# Frame Weight
#A0032-2P



Private Label Machines
7 Stock Colors
Plus Chrome



Tampico Polishing & Scrubbing Brush
#A0021 - 13"
#A0035 - 15"
#A0004 - 17"
#A0005 - 20"



Stiff Poly Scrub Brush
For General Scrubbing
#A0020 - 13"
#A0036 - 15"
#A0002 - 17"
#A0003 - 20"



Lite Grit Brush
Scrub with Flexible
Blue 150 Grit Bristles
#A0018-1 - 13"
#A0038-1 - 15"
#A0008-1 - 17"
#A0009-1 - 20"




Grit Brush
Strip/Scrub with Stiff
Black 80 Grit Bristles
#A0018 - 13"
#A0038 - 15"
#A0008 - 17"
#A0009 - 20"



Nylon Carpet Brush
Scrub with soft & stiff
nylon bristle mix
#A0016 - 13"
#A0037 - 15"
#A0006 - 17"
#A0007 - 20"



Hawk Safe Spin Carpet Brush w/Adjustable S/S Glide Plate
Smooth adjustable plate protects the carpet
#A0013-17 - 17"
#A0013-20 - 20"




Tufted Pad Driver
3/4" long stiff poly bristles, 3/4" riser
#1007 - 12"
#A0018-1 W/R - 13"
#A0010-4 - 17"
#A0011-3 - 20"



Premium Double Hook Pad Driver w/ Riser
#A0017 - 13"
#A0034 - 15"
#A0010 - 17"
#A0011 - 20"



Premium Sandpaper Driver
Plywood block, cushion pad, 1" riser.
A0014-HD - 17"
A0014-1HD - 20"



Economy Sandpaper Driver
Molded plastic block, cushion pad, 1" riser
#A0014 - 17"
#A0014-1 - 20"




Surface Prep Scraper
(6) Tungsten Steel Blades, Steel Clutch Plate
#HP0035 - 13"
#HP0033 - 17"
#HP0034 - 20"



Orbitec Diamond Driver
(6) Cups Hold 3" Diamond Tools. Steel Clutch Plate.
#HP0018 - 13"
#HP0017-3 - 17"
#HP0020-3 - 20"



Tri-Headed Orbitec Diamond Driver
Holds 6" and 8" Pads and Brushes.
Steel Clutch Plate
#HP0015 - 16x6"
#HP0015-8 - 16x8"




Diamond Pad Driver
#A0017DPD - 13"
#A0034 - 15"
#A0010DPD - 17"
#A0011DPD - 20"




Weighted Diamond Pad Driver
Steel Block & Clutch Plate
#A0017WTDPD - 12" (25#)
#A0010WTDPD - 17" (46#)
#A0011WTDPD - 20" (64#)



HAWK Claw Diamond Disc Driver
#CLAW13 - 13"
#CLAW15 - 15"
#CLAW17 - 17"
#CLAW20 - 20"



Red Buffing Pad
(5 Pack)
#A0026-13R-CS- 13"
#A0026-15R-CS- 15"
#A0026-17R-CS- 17"
#A0026-20R-CS- 20"



Black Stripping Pad
(5 Pack)
#A0026-17BK-CS- 13"
#A0026-17BK-CS- 15"
#A0026-17BK-CS- 17"
#A0026-20BK-CS- 20"



Pad Centering Clamp
Pad Mount - 2 Piece Design
#KIT2013 - Screw Lock
#KIT2014 - Spring Lock

*Rotary brush blocks are 2" smaller than machine size. Rotary pad driver blocks are 1" smaller than machine size. All have Universal clutch plate.