



Dry Stripping, Scrubbing, Stripping



The TigerHawk 2014 with the revolutionary rectangular “floating head” design is easy to maneuver, with less vibration, sound and operator fatigue than other orbiting brands. Works faster than rotary machines, easily reaches into corners and along baseboards. Use the spray system model (TH2014-SP) or active vacuum system model (TH2014-V) for even greater productivity. Add the 4.5 gallon solution tank for wet scrubbing. Strip large areas of floor finish with or without chemicals. The 2014 is excellent for sanding, scrubbing and stone stripping.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 2-pc. 12-3 SJTOW industrial power cord with molded plug

Drive System

- Eccentric balanced orbital drive works at 1725 RPM

Engineered Design

- Dual vibration isolation system
- Heavy duty powder-coated steel handle with 5-position pin lock
- The WD™ handle is easy to remove for transport and storage
- The severe-duty motor guard to protect from impact damage
- Includes easy to move transport cart
- The severe-duty motor guard mounts on the motor
- 2” x 8” non-marking ball bearing wheels
- The 2014 frame is built with a vacuum port. The 2014 “V” model connects here with 6 quart tank vacuum and dust skirt.
- The 2814 “SP” model adds motor-mounted solution pump and handle-mounted 4.5 gallon solution tank

Safety Features

- Quiet 60 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model	TH-2014	TH2014-SP	TH2014-V
Part Number	F-TIGER2014	F-TIGER 2014-SP	F-TIGER2014-V
Pad Size	20” x 14”	20” x 14”	20” x 14”
Configuration	Standard	w/ Solution Pump & 4.5 Gal. Solution Tank	w/ 6 Qt. Tank Vacuum & Skirt
Pad Speed	1740 RPM	1740 RPM	1740 RPM
Amp Draw	7.1 Amp	7.1 Amp	11.8 Amp
Weight	250 lbs.	259 lbs.	269 lbs.
Pad Pressure	0.89 lbs/in ²	0.92lbs/in ²	0.96 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft. 2-pc. 12-3 SJTOW industrial power cord w/molded plug
Drive System	Eccentric balanced orbital drive
Vibration Isolators	(6) primary, (8) secondary isolaters
dB Rating	60 dB - Meets GS42 standard

Subject to Change Without Notice



TH2014-V Model Adds the 6 Quart Tank Vac and Dust Skirt



TH2014-SP Model Adds the Spray Pump and Solution Tank



Steel Frame with Rear Vacuum Port



Works Along Baseboards and Into Corners



HAWK TigerHawk 2014 Orbital Floor Machine Accessories




Dust Control Kit
Dust Skirt & Hardware
#HP0031-DC-TIGER2014



Vacuum Assembly Kit
6 Quart Tank Vac,
Dust Skirt & Hardware
#FM1011-2014



**4.5 Gallon
Solution Tank**
#SME-0193-INATASSY



Orbital Scrub Brush
20" x 14"
#A0076-2014




**Red Orbital
Scrubbing Pads**
5 Case




**Black Orbital
Stripping Pads**
5 Case




**Green Astro Textured
Surface Pads**
4 Case



**Hawk Surface
Prep Pads
Maroon**
10 Case



Orbital Pad Starter Kit
(1) Green, (1) Red
(2) Black, (2) Maroon



Abrasive Screens
10 Case

Orbital Pad Color	10" x 14" for TigerHawk 1410	20" x 14" for TigerHawk 2014 G2 Raptor, Red Tail	28"x14" For TigerHawk 2814
Red (5/cs.)	A0066-1410-CS	A0066-2014-CS	A0066-2814-CS
Black (5/cs.)	A0069-1410-CS	A0069-2014-CS	A0069-2814-CS
Green Astro (4/cs.)	A0072-1410-CS	A0072-2014-CS	A0072-2814-CS
Maroon (10/cs.)	A0064-1410-CS	A0064-2014-CS	A0064-2814-CS
Orbital Starter Kit (1 black, 1 green, 1 red, 2 maroon)	A0075-1410PADKIT	A0075-2014PADKIT	A0075-2814PADKIT
Red Heat Screen 80 Grit	A0074-1410-80	A0074-2014-80	A0074-2814-80
Red Heat Screen 120 Grit	A0074-1410-120	A0074-2014-120	A0074-2814-120
Red Heat Screen 180 Grit	A0074-1410-180	A0074-2014-180	A0074-2814-180