



Dry Stripping, Scrubbing, Stripping



The TigerHawk 2014 with the revolutionary rectangular “floating head” design is easy to maneuver, with less vibration, sound and operator fatigue than other orbiting brands. Works faster than rotary machines, easily reaches into corners and along baseboards. Use the spray system model (TH2014-SP) or active vacuum system model (TH2014-V) for even greater productivity. Strip large areas of floor finish with or without chemicals. The 2014 is excellent for sanding, scrubbing and stone stripping.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 2-pc. (12-3) SJTOW industrial power cord with molded plug

Drive System

- Eccentric balanced orbital drive works at 1725 RPM

Engineered Design

- Dual vibration isolation system
- Powder-coated heavy duty steel handle with 5-position pin lock
- The WD™ handle is easy to remove for transport and storage
- The severe-duty motor guard to protect from impact damage
- Includes easy to move transport cart
- The severe-duty motor guard mounts on the motor
- 2" x 8" non-marking ball bearing wheels
- 2014 drive frame is built with a vacuum port. The vacuum “V” model connects here with 6 quart tank vacuum and dust skirt.
- Spray “SP” model adds motor-mounted solution pump and handle-mounted 4.5 gallon solution tank

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model	TH-2014	TH2014-SP	TH2014-V
Part Number	F-TIGER2014	F-TIGER 2014-SP	F-TIGER2014-V
Pad Size	20" x 14"	20" x 14"	20" x 14"
Configuration	Standard	w/ Solution Pump & 4.5 Gal. Solution Tank	w/ 6 Qt. Tank Vacuum & Skirt
Pad Speed	1725 RPM	1725 RPM	1725 RPM
Amp Draw	7.1 Amp	7.1 Amp	11.8 Amp
Weight	250 lbs.	259 lbs.	269 lbs.
Pad Pressure	0.89 lbs/in ²	0.92lbs/in ²	0.96 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft., 2-pc. (12-3) SJTOW industrial power cord w/molded plug
Drive System	Eccentric balanced orbital drive
Vibration Isolators	(6) primary, (8) secondary isolaters
dB Rating	66 dB - Meets GS42 standard

Subject to Change Without Notice



Works Along Baseboards and Into Corners



TH2014-SP Model Adds the Spray Pump and Solution Tank



Steel Frame with Rear Vacuum Port



Works Along Baseboards and Into Corners