



Dry Stripping, Scrubbing, Stripping

The TigerHawk 2814 with the revolutionary rectangular “floating head” design is easy to maneuver, with less vibration, sound and operator fatigue than other orbiting brands. Works 3 times faster than rotary machines, easily reaches into corners and along baseboards. Use the spray system model (TH2814-SP) or active vacuum system model (TH2814-V) for even greater productivity. Strip large areas of floor finish with or without chemicals. The 2814 is excellent for sanding, scrubbing and stone stripping.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 2-pc. 12-3 SJTOW industrial power cord with molded plug

Drive System

- Eccentric balanced orbital drive works at 1740 RPM

Engineered Design

- Dual vibration isolation system
- Heavy duty powder-coated steel handle with 5-position pin lock
- The WD™ handle is easy to remove for transport and storage
- The severe-duty motor guard to protect from impact damage
- Includes easy to move transport cart
- Thumb-operated safety switch. Dual steel operating triggers.
- Includes full wraparound dust skirt
- 2” x 8” non-marking ball bearing wheels
- The 2814 frame is built with dual vacuum ports. The 2814 “V” model connects here with 6 quart tank vacuum and dust skirt.
- The 2814 “SP” model adds motor-mounted solution pump and handle-mounted 4.5 gallon solution tank

Safety Features

- Quiet 60 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model	TH-2814	TH2814-SP	TH2814-V
Part Number	F-TIGER2814	F-TIGER 2814-SP	F-TIGER2814-V
Pad Size	28” x 14”	28” x 14”	28” x 14”
Configuration	Standard	w/ Solution Pump & 4.5 Gal. Solution Tank	w/ 6 Qt. Tank Vacuum & Skirt
Pad Speed	1740 RPM	1740 RPM	1740 RPM
Amp Draw	7.8 Amp	7.8 Amp	12.5 Amp
Weight	305 lbs.	314 lbs.	324 lbs.
Pad Pressure	0.78 lbs/in ²	0.80lbs/in ²	0.82 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft. 2-pc. 12-3 SJTOW industrial power cord w/molded plug
Drive System	Eccentric balanced orbital drive
Vibration Isolators	(8) primary, (8) secondary isolaters
dB Rating	60 dB - Meets GS42 standard


Subject to Change Without Notice



TH2814-V Model Adds the 6 Quart Tank Vac and Dust Skirt



TH2814-SP Model Adds the Spray Pump and Solution Tank



Frame is Built with Dual Vacuum Ports



Includes Transport Cart



HAWK TigerHawk 2814 Orbital Floor Machine Accessories



Dust Control Kit
Dust Skirt & Hardware
#HP0031-DC-TIGER2814



Vacuum Assembly Kit
6 Quart Tank Vac,
Dust Skirt & Hardware
#FM1011-2814



**4.5 Gallon
Solution Tank**
#SME-0193-INATASSY



Orbital Scrub Brush
28" x 14"
#A0076-2814



**Red Orbital
Scrubbing Pads**
5 Case




**Black Orbital
Stripping Pads**
5 Case




**Green Astro Textured
Surface Pads**
4 Case



**Hawk Surface
Prep Pads
Maroon**
10 Case



Orbital Pad Starter Kit
(1) Green, (1) Red
(2) Black, (2) Maroon



Abrasive Screens
10 Case

Orbital Pad Color	10" x 14" for TigerHawk 1410	20" x 14" for TigerHawk 2014 G2 Raptor, Red Tail	28"x14" For TigerHawk 2814
Red (5/cs.)	A0066-1410-CS	A0066-2014-CS	A0066-2814-CS
Black (5/cs.)	A0069-1410-CS	A0069-2014-CS	A0069-2814-CS
Green Astro (4/cs.)	A0072-1410-CS	A0072-2014-CS	A0072-2814-CS
Maroon (10/cs.)	A0064-1410-CS	A0064-2014-CS	A0064-2814-CS
Orbital Starter Kit (1 black, 1 green, 1 red, 2 maroon)	A0075-1410PADKIT	A0075-2014PADKIT	A0075-2814PADKIT
Red Heat Screen 80 Grit	A0074-1410-80	A0074-2014-80	A0074-2814-80
Red Heat Screen 120 Grit	A0074-1410-120	A0074-2014-120	A0074-2814-120
Red Heat Screen 180 Grit	A0074-1410-180	A0074-2014-180	A0074-2814-180