



Dry Stripping, Scrubbing, Stripping

The TigerHawk 2814 with the revolutionary rectangular “floating head” design is easy to maneuver, with less vibration, sound and operator fatigue than other orbiting brands. Works 3 times faster than rotary machines, easily reaches into corners and along baseboards. Use the spray system model (TH2814-SP) or active vacuum system model (TH2814-V) for even greater productivity. Strip large areas of floor finish with or without chemicals. The 2814 is excellent for sanding, scrubbing and stone stripping.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft., (12-3) SJTOW industrial power cord with molded plug

Drive System

- Eccentric balanced orbital drive works at 1725 RPM

Engineered Design

- Dual vibration isolation system
- Powder-coated heavy duty steel handle with 5-position pin lock.
- The WD™ handle is easy to remove for transport and storage
- The severe-duty motor guard to protect from impact damage
- Includes easy to move transport cart
- Thumb-operated safety switch. Dual steel operating triggers.
- Includes full wraparound dust skirt
- 2” x 8” non-marking ball bearing wheels
- Built with two vacuum ports for use with on "V" models
- The “SP” model adds a 45 PSI spray pump and 4.5 gallon solution tank.

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model	TH-2814	TH2814-SP	TH2814-V
Part Number	F-TIGER2814	F-TIGER 2814-SP	F-TIGER2814-V
Pad Size	28” x 14”	28” x 14”	28” x 14”
Configuration	Standard	w/ Solution Pump & 4.5 Gal. Solution Tank	w/ 6 Qt. Tank Vacuum & Skirt
Pad Speed	1725 RPM	1725 RPM	1725 RPM
Amp Draw	7.8 Amp	7.8 Amp	12.5 Amp
Weight	305 lbs.	314 lbs.	324 lbs.
Pad Pressure	0.78 lbs/in ²	0.80 lbs/in ²	0.82 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft., 2-pc, (12-3) SJTOW industrial power cord w/molded plug
Drive System	Eccentric balanced orbital drive
Vibration Isolators	(8) primary, (8) secondary isolaters
dB Rating	66 dB - Meets GS42 standard

Subject to Change Without Notice



Frame is Built with Dual Vacuum Ports for Use on TH2814-V



TH2814-SP Adds a Sprayer Pump & 4.5 Gallon Solution Pump



Includes Full Wrap-Around Dust Skirt



Includes Transport Cart