



Stripping, Scrubbing, Buffing



The BlackHawk has been redesigned for easy transport in today's smaller vehicles. The exclusive Pin-Set™ Handle Lock does away with nuisance adjustments that are common with friction handle locks. Steel construction with commercial-quality components include ball bearing wheels, commercial grade cord and grips, a solid steel handle lock and the durable 1.5 HP dual-capacitor motor. The BlackHawk buffer can deliver 24/7 reliable results for years to come.

Power

- 1.5 HP, 66 frame, rectified dual capacitor motor
- 115V, 60 Hz power. Strain relief (14-3) STO power cord

Drive System

- Triple-planetary 10:1 helical-cut commercial gears drive pads and brushes at 175 RPM

Engineered Design

- The all steel detachable handle with pin-set handle lock disassembles in 60 seconds, no tools required.
- Quality welded steel construction
- Pin Set™ Handle Lock adjusts the handle to 4 heights
- 17" or 20" brush covers. 360 degree wraparound bumpers.
- Thumb-operated safety switch. Dual steel operating trigger.
- Negative pressure on/off switch
- Optional 4 gallon solution tank in 5 stock colors
- Optional Splash Guard #SPLASH17 or #SPLASH20
- Sturdy 1" x 5" non-marking ball bearing wheels
- Includes Hawk Lok™ molded plastic pad driver

Safety Features

- Quiet 62 dB operation. Meets GS42 standard.
- Built with UL approved components



Specifications

Model #	BLKHWK17	BLKHWK20
Part #	F0009-BH2P	F0012-BH2P
Machine Size	17"	20"
Pad Size	16"	19"
Pad Speed	175 rpm	175 rpm
Amp Draw	5.9 Amp	6.5 Amp

All Models

Motor	66 frame, 1.5 HP rectified DC motor
Power	115V / 60 Hz (230V Option)
Power Cord	50 ft. (14-3) STO power cord with molded plug
Drive System	Triple-planetary 10:1 helical-cut gears
dB Rating	62 dB - Meets GS42 standard

Subject to Change Without Notice



Remove/Install the Handle in 60 Seconds



Exclusive Pin-Set™ Handle Lock - 4 Height Settings



Remove the Handle Mounting Pin w/o Tools



Includes Hawk Lok™ Pad Driver