



Stripping, Scrubbing, Buffing



The BlackHawk has been redesigned for easy transport in today's smaller vehicles. The exclusive Pin-Set™ Handle Lock does away with nuisance adjustments that are common with friction handle locks. Steel construction with commercial-quality components include ball bearing wheels, commercial grade cord and grips, a solid steel handle lock and the durable 1.5 HP dual-capacitor motor. The BlackHawk buffer can deliver 24/7 reliable results for years to come.

Power

- 1.5 HP dual capacitor AC motor
- 115V, 60 Hz (50 Hz optional) power
- 50 ft., (14-3) 2-piece commercial power cord with cord lock

Drive System

- **BlackHawk** uses triple-planetary HD 10:1 helical-cut commercial gears. Drives brushes and pads at 175 RPM
- **BlackHawk XHD** (Extra Heavy Duty) planetary 11:1 helical-cut industrial gears, case hardened with steel coupler. Drives brushes and pads at 165 RPM

Engineered Design

- The all steel 2-piece unit detachable handle with pin-set handle lock disassembles in 60 seconds, no tools required
- Quality welded steel construction
- Pin Set™ Handle Lock adjusts the handle to 4 heights
- 17" or 20" brush covers with 360 degree gray wraparound bumpers
- Thumb-operated safety switch. Dual steel operating trigger
- Negative pressure on/off switch
- Sturdy 1" x 5" non-marking ball bearing wheels
- Includes Tufted Bristled Pad Driver (#A0010-4 - 17") or (#A0011-3- 20")
- Optional 4 gallon solution tank (#A0001-NAT4)
- Optional Splash Guard (#SPLASH17) or (#SPLASH20)
- Optional handle mounted power cord wrap (#KIT3009-1BLK)

Safety Features

- Quiet 62 dB operation. Meets GS42 standard
- Built with UL listed components



Specifications

Model	BlackHawk 17	BlackHawk XHD 17	BlackHawk 20	BlackHawk XHD 20
Item #	F50-17	F51-17	F50-20	F51-20
Machine Size	17"	17"	20"	20"
Pad Size	16"	16"	19"	19"
Pad Speed	175 rpm	175 rpm	175 rpm	175 rpm
Amp Draw	5.9	6.5	6.1	6.8
Weight	94 lbs.	97 lbs.	94 lbs.	97 lbs.

All Models

Motor	1.5 HP, dual capacitor AC
Power	115V-230V. 60 Hz (50 Hz Optional)
Power Cord	50 ft., (14-3) 2-piece commercial w/ cord lock
Drive System	Triple-planetary 10:1 helical-cut gears
Sound Level (Ave.)	62 dB - Meets GS42 standard

Subject to Change Without Notice




Remove/Install the Handle in 60 Seconds



Exclusive Pin-Set™ Handle Lock - 4 Height



Remove the Handle Mounting Pin w/o Tools



Includes Stiff Bristle Pad Driver