



### Burnishing, Refinishing



The BlackHawk HSB Burnisher drives a 20" pad at 1500, 1800 or 2000 RPM for efficient polishing of all hard floor finishes. The 1.5 HP, 66 frame DC motor is powerful. The welded steel frame and chromed handle are durable and reliable.

**Power**

- 1.5 HP, 66 frame, DC rectified motor
- 115V, 60 Hz power
- 50 ft. 14-3 STO industrial power cord with molded plug

**Drive System**

- A 10-groove V-Belt drives pads at 1500, 1800 or 2000 RPM

**Engineering Design**

- Welded heavy gauge steel frame
- One piece chromed heavy-duty steel handle
- Molded plastic brush cover with wraparound bumper
- Thumb-operated safety switch
- Comfortable vinyl grips
- Negative pressure on/off switch. Dual steel operating triggers.
- Multiple position handle adjustment
- Non-marking 1" x 5" non-marking ball bearing wheels
- Includes flexible pad driver with spring-style pad centering clamp (KIT2014)

**Safety Features**

- Quiet operation - 66 dB. Meets GS42 standard.
- Built with UL listed components



### Specifications

	BLKHWK 1500	BLKHWK 1800	BLKHWK 2000
<b>Model</b>	BLKHWK 1500	BLKHWK 1800	BLKHWK 2000
<b>Part#</b>	F1500-20-BH	F1800-20-BH	F2000-20-BH
<b>Pad Speed</b>	1500 RPM	1800 RPM	2000 RPM
<b>Motor</b>	1.5 HP, 66 frame DC rectified motor		
<b>Drive System</b>	Multi V-belt drive		
<b>Power</b>	115V, 50/60 Hz power		
<b>Cord</b>	50 ft. 14-3 STO power cord with molded plug		
<b>Pad Size</b>	20"		
<b>Amp Draw</b>	13.5 Amp		
<b>dB Rating</b>	66 dB - Meets GS42 standard		
<b>Weight</b>	92 lbs.		

Subject to Change Without Notice



All Steel Construction Handle, Frames



Flexible Pad Driver with Pad Centering Clamp



Use with 20" Hogs Hair Pads and Centering Clamp



Optional Splash Guard **SPLASH20 - 20"**



**BlackHawk 1500 Burnisher Accessories**



**Splash Guard**  
**#SPLASH20 - 20"**



Includes Flexible  
Pad Driver with  
Centering Clamp



**Hogs Hair  
Burnishing Pads**  
(5 Pack)  
**#A0025-19P-CS- 19"**  
**#A0025-20P-CS- 20"**



**Pad Centering  
Clamp**  
Spring Mount  
**#KIT2014**