



## Dry Floors, Circulate & Exhaust Air

Hawk Industrial Air Mover with 1/2 HP, 3-speed industrial motor will move air consistently to 2950 CFM. Built with super-tough polypropylene housing for long-term use in the toughest of applications; construction, manufacturing and housekeeping applications. Metal cage and safety discharge guard.

### Power

- 0.5 HP, 3-speed motor
- 115V, 50/60 Hz power. 230V available.
- 12 Amp draw with circuit breaker
- 25 ft. 16-3 SJTOW power cord with molded plug
- Top mounted, quick change 3-speed switch

### Engineering Design

- Three air flow speeds - 2000 CFM, 2500 CFM and 2950 CFM with switch on housing
- Continuous-duty rugged ball bearing motor
- Polyethylene housing with extended warranty
- Plastic fan wheel
- Steel handle and air discharge guard
- 8 rubber feet for non-slip positioning
- Stackable for easy storage
- Convenient size - 19.5" x 14.5" x 18.25"
- Available in 2 colors; royal blue, and black. Special colors with 25 piece order.

### Safety Features

- UL Listed
- Quiet operation with dB levels: Low 59, Medium 62, High 64. Meets GS42 standard.



### Specifications

<b>Model#</b>	<b>BH001-3S</b>		
<b>Part #</b>	<b>BH001-BLK, BH001-RYB</b>		
<b>Motor</b>	0.5 HP, 3-speed motor		
<b>Power</b>	115V, 50/60 Hz power		
<b>Motor CFM</b>	2000 CFM	2500 CFM	2950 CFM
<b>Amp Draw</b>	4.3 Amp	4.5 Amp	5.3 Amp
<b>Power Cord</b>	25 ft. 16-3 SJTOW power cord w/molded plug		
<b>Housing</b>	Polyethylene housing		
<b>Auxiliary Outlet</b>	12 Amp with circuit breaker		
<b>Positions</b>	0, 45 and 90 degrees		
<b>dB Rating</b>	59 dB (low speed), 62 dB (medium), 64 dB (high). Meets GS42 standard.		
<b>Size</b>	19.5" x 14.5" x 18.25"		
<b>Weight</b>	31 lbs.		

Subject to Change Without Notice



Frame in Royal Blue and Black



Metal Carrying Handle



3-Speed Switch