



Dry Stripping, Scrubbing, Stripping

The TigerHawk 2014 revolutionary rectangular floating head is easy to maneuver with less vibration, noise and fatigue than other orbiting brands. The WD™ handle design assures 100% pad contact with the floor. The 2014 works three times faster than rotary floor machines, easily reaching into corners and along baseboards. Add a handle mounted vacuum tank for dust control. Add the 4 gallon solution tank for wet scrubbing.

The TigerHawk 2014 can strip large areas of floor finish with or without chemicals. The 2014 is excellent for sanding, scrubbing and stone stripping. Easy to learn. Easy to use.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 2-Part 12-3 SJTOW industrial power cord with molded plug

Drive System

- Essentric balanced orbital drive works at 1725 RPM

Engineered Design

- Dual vibration isolation system
- The WD™ powder coated, heavy duty steel handle is easy to remove for transport and storage
- 5-position pin lock handle adjustment and vinyl grips
- The severe-duty motor guard mounts on the motor to protect from impact damage
- 2" x 8" non-marking ball bearing wheels.
- Thumb-operated safety switch. Dual steel operating triggers.
- Negative pressure on/off switch.
- 2014 drive plate is built with a vacuum port. The vacuum "V" model connects here with 6 quart tank vacuum and dust skirt.
- Spray "SP" model adds motor-mounted solution pump and handle-mounted 4.5 gallon solution tank

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed

Specifications

Model	TH-2014	TH2014-SP	TH2014-V
Part Number	F-TIGER2014	F-TIGER 2014-SP	F-TIGER2014-V
Pad Size	20" x 14"	20" x 14"	20" x 14"
Configuration	Standard	w/ Solution Pump & 4.5 Gal. Solution Tank	w/ 6 Qt. Tank Vacuum & Skirt
Pad Speed	1725 RPM	1725 RPM	1725 RPM
Amp Draw	7.1 Amp	7.1 Amp	11.8 Amp
Weight	250 lbs.	259 lbs.	269 lbs.
Pad Pressure	0.89 lbs/in ²	0.92lbs/in ²	0.96 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft., 2-Part 12-3 SJTOW industrial power cord w/molded plug
Drive System	Essentric balanced orbital drive
Vibration Isolators	(6) primary, (8) secondary isolaters
dB Rating	66 dB - Meets GS42 standard

Subject to Change Without Notice



Works Along Baseboards and Into Corners



TH2014-SP Model Adds the Spray Pump and Solution Tank



Steel Frame with Rear Vacuum Port



TH2014-V Model Adds the 6 Quart Tank Vac, Dust Skirt and Hoses



TigerHawk 2014 Accessories



Full Wraparound
Dust Skirt
HP0031-DC-TIGER2014



Vacuum Assembly Kit
TH1011



2014 with 4.5 Gallon
Solution Tank & Spray
Pump
TH2014-SP
TH1010 (Kit)



4.5 Gallon
Solution Tank
SME0193-THASSY


Orbital Pads



20"x14" Red Orbital
Scrubbing Pads - 5 Case
A0066-2014-CS




20"x14" Black Orbital
Stripping Pads - 5 Case
A0069-2014-CS



20"x14" Green Orbital
Scrubbing Pads - 5 Case
A0072-2014-CS



20"x14" Maroon
Chemical Free Pads
5 Case
A0064-2014-CS



20"x14" Orbital Pads
Starter Kit
(1) Green Astro, (1) Red
(1) Black, (2) Maroon
A0075-2014-PADKIT

Orbital Abrasive Screens



20x14" Abrasive Screen
A0074-2014-80 - 80 Grit
A0074-2014-120 - 120 Grit
A0074-2014-180 - 180 Grit