



Dry Stripping, Scrubbing, Stripping

The TigerHawk 2814 with the revolutionary rectangular floating head is easy to maneuver, with less vibration, sound and fatigue than other orbiting brands. The WD™ handle design assures 100% pad contact with the floor. The 2814 works three times faster than rotary floor machines, easily reaching into corners and along baseboards. Use the spray system model or active vacuum system model for even greater productivity.

The TigerHawk 2814 can strip large areas of floor finish with or without chemicals. The 2814 is excellent for sanding, scrubbing and stone stripping. Easy to learn. Easy to use.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft., 12-3 SJTOW industrial power cord with molded plug

Drive System

- Essentric balanced orbital drive works at 1725 RPM

Engineered Design

- Dual vibration isolation system
- The WD™ powder coated, heavy duty steel handle is easy to remove for transport and storage
- The severe-duty motor guard mounts on the motor to protect from impact damage
- Includes easy to move transport cart
- 5-position pin lock handle adjustment and vinyl grips
- Thumb-operated safety switch. Dual steel operating triggers.
- Includes full wraparound dust skirt
- 2" x 8" non-marking ball bearing wheels
- Built with two vacuum ports for use with on "V" models with the 6.5 quart tank vacuum
- The "SP" model adds a 45 PSI spray pump and 4.5 gallon solution tank

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model	TH-2814	TH2814-SP	TH2814-V
Part Number	F-TIGER2814	F-TIGER 2814-SP	F-TIGER2814-V
Pad Size	28" x 14"	28" x 14"	28" x 14"
Configuraation	Standard	w/ Solution Pump & 4 Gal. Solution ank	w/ 6.5 Qt. Tank Vacuum & Skirt
Pad Speed	1725 RPM	1725 RPM	1725 RPM
Amp Draw	7.8 Amp	7.8 Amp	12.5 Amp
Weight	305 lbs.	314 lbs.	324 lbs.
Pad Pressure	0.78 lbs/in ²	0.80 lbs/in ²	0.82 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft., 2- art 12-3 SJTOW industrial power cord w/molded plug
Drive System	Essentric balanced orbital drive
Vibration Isol tors	(6) primary, (8) secondary isolaters
dB Rating	66 dB - Meets GS42 standard.


Subject to Change Without Notice



Includes Full Wrap-Around Dust Skirt



Includes Transport Cart



Frame is Built with Dual Vacuum Ports for Use on TH2814-V



TH2814-SP Adds a Sprayer Pump & 4.5 Gallon Solution Pump



TigerHawk 2814 Accessories



Wrap-Around Dust Apron
HP0031-DC-TIGER2814



Vacuum Assembly Kit
TH1011



4.5 Gallon Solution Tank
SME0193-THASSY



TigerHawk Optional Power
Spray Assembly
TH1010 Kit


Orbital Pads



28"x14" Red Orbital
Scrubbing Pads - 5 Case
A0066-2814-CS




28"x14" Black Orbital
Stripping Pads - 5 Case
A0069-2814-CS



28"x14" Green Orbital
Stripping Pads - 5 Case
A0068-2814-CS




28"x14" Maroon
Chemical Free Pads
5 Case
A0064-2014-CS



28"x14" Orbital Pads
Starter Kit
(1) Green Astro, (1) Red
(1) Black, (2) Maroon
A0075-2814-PADKIT

Orbital Abrasive Screens



28"x14" Abrasive Screen
A0074-2814-80 - 80 Grit
A0074-2814-120 - 120 Grit
A0074-2814-180 - 180 Grit