



Stripping, Scrubbing, Polishing

Machine operators will appreciate the performance, versatility and value in the Hawk Mighty. The 1.0 HP TEFC AC motor and XHD gears deliver huge power in a small and manageable machine. It's ideal for use in tight spaces, restrooms, edging and stairs.

The TH models, with telescoping handle, fit every operator's height and store in tight spaces.

Power

- 1.0 HP, 56C frame, dual capacitor, AC motor
- 115-230V , 50/60 Hz power
- 50 ft. 14-3 SJT power cord with molded plug

Drive System

- Triple-planetary Severe-Duty 11:1 helical-cut industrial gears, case hardened with steel coupler
- Gears drive brushes and pads at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- Telescoping handle (TH models) adjusts from 36" to 48"
- 13" and 15" steel brush covers with full wraparound bumper
- One piece powder-coated, heavy duty steel handle with 6-position pin lock
- Comfortable vinyl handle grips
- Thumb-operated safety switch. Negative pressure on/off switch.
- Dual steel operating triggers
- 1"x5" non-marking ball bearing wheels

Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components



Specifications

Model	MIGHTY13	MIGHTY 13-TH	MIGHTY15	MIGHTY15-TH
Part #	F0060-13	F0060-13TH	F0060-15	F0060-15TH
Size	13"	13"	15"	15"
Pad Size	12"	12"	14"	14"
Telescoping Handle	No	Yes	No	Yes
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	4.9 Amp	4.9 Amp	6 Amp	6 Amp
Weight	87 lbs.	87 lbs.	88 lbs.	88 lbs.

All Models	
Motor	1.0 HP, 56 frame, dual capacitor AC motor
Power Source	115-230V, 50/60 Hz power
Power Cord	50 ft. 14-3 SJT power cord w/molded plug
Driver System	Triple-planetary XHD 11:1 helical-cut industrial gears
dB Rating	64 dB - Meets GS42 standard

Subject to Change Without Notice



Works in Tight Spaces



Telescoping Handle Adjusts from 36" to 48"



Optional 2.5-Gallon Solution Tank



Handle with 6-Position Pin Lock



HAWK Mighty Accessories



Splash Guard
#SPLASH13 - 13"
#SPLASH15 - 15"



Private Branded Machines
7 Stock Colors
Plus Chrome



2.5 Gallon Solution Tank
#A001-BLK25 - Black



Tampico Polishing / Scrubbing Brush
#A0021 - 13"
#A0035 - 15"



Stiff Poly Scrub Brush
For general scrubbing
#A0020 - 13"
#A0036 - 15"




Lite Grit Brush
Scrub with flexible blue 150 grit bristles
#A0018-1 - 13"
#A0038-1 - 15"




Grit Brush
Strip/scrub with stiff black 80 grit bristles
#A0018 - 13"
#A0038 - 15"



Nylon Carpet Brush
Scrub with soft & stiff nylon bristle mix
#A0016 - 13"
#A0037 - 15"



Tufted Stiff Poly Bristle Pad Driver
3/4" long bristles, 3/4" riser
#1007 - 12"
#A0018-1 W/R - 13"




Diamond Pad Driver
#A0017DPD - 13"
#A0034 - 15"



Weighted Diamond Pad Driver
Steel block & clutch plate
#A0017WTDPD - 12" (25#)



Red Buffing Pad (5 Pack)
Use at 175-600 RPM for everyday cleaning and light scrubbing.
#A0026-13R-CS - 13"
#A0026-15R-CS - 15"



Black Stripping Pad (5 Pack)
Heavy-duty scrubbing and for removal of 2-4 coats of finish/sealer
#A0026-13BK-CS - 13"
#A0026-15BK-CS - 15"




Pad Centering Clamp
Pad mount - 2 piece design
#KIT2013 - Screw Lock
#KIT2014 - Spring Lock



Surface Prep Scraper
(6) tungsten steel blades, steel clutch plate
#HP0035 - 13"



Orbitec Diamond Driver
(6) cups hold 3" diamond tools, steel clutch plate
#HP0018 - 13"



HAWK Claw Diamond Disc Driver
#CLAW13 - 13"
#CLAW15 - 15"

*Rotary brush blocks are 2" smaller than machine size. Rotary pad driver blocks are 1" smaller than machine size. All have Universal clutch plate.