



Dry Floors, Circulate & Exhaust Air

Hawk Industrial Air Mover with 1/2 HP, 3-speed industrial motor will move air consistently to 2950 CFM. Built with super-tough polyethylene frame for long-term use in the toughest of applications; construction, manufacturing, and house keeping applications. Metal cage and safety discharge guard.

Power

- 0.5 HP, 3-speed motor
- 115V, 50/60 Hz power. 230V available.
- 12 Amp draw with circuit breaker
- 25 ft., 16-3 SJTOW power cord with molded plug
- Top mounted, quick change 3-speed switch

Engineering Design

- Three air flow speeds - 2950 CFM, 2500 CFM and 2000 CFM with switch on frame
- Continuous-duty rugged ball bearing motor
- Polyethylene housing with lifetime warranty
- Metal cage and air discharge guard
- Steel handle
- 4 rubber feet for non-slip positioning
- Stackable for easy storage
- Convenient size - 19.5" x 14.5" x 18.25"
- Available in 2 colors; medium blue, and black. Special colors with 25 pieces.

Safety Features

- UL Listed
- Quiet operation with sound levels: Low 59, Medium 62, High 64. Meets GS42 standard.



Specifications

Model#	BH001-3S		
Part #	BH001-BLACK, BH001-DKBLUE		
Motor	0.5 HP, 3-speed motor		
Power	115V, 50/60 Hz power		
Motor CFM	2000 CFM	2500 CFM	2950 CFM
Amp Draw	4.3 Amp	4.5 Amp	5.3 Amp
Power Cord	25 ft., 16-3 SJTOW power cord w/molded plug		
Housing	Polyethylene housing		
Auxiliary Outlet	12 Amp with circuit breaker		
Positions	0, 45 and 90 degrees		
dB Rating	59 dB (low speed), 62 dB (medium), 64 dB (high). Meets GS42 standard.		
Size	19.5" x 14.5" x 18.25"		
Weight	31 lbs.		

Subject to Change Without Notice



Frame in Blue and Black



Metal Carrying Handle



3-Speed Switch