



17" & 20" Glide Sanding with Dust Control



The Glide Sanding Star starts with the Glide Freedom floor machine, and adds a 6 quart tank vacuum with triple filters mounted on the handle carriage - maintaining the engineered machine head weight and machine balance. The Sanding Star is powered by a super-strong, 1.25 HP TEFC AC motor with XHD Industrial 11:1 ratio gears driving sanding tools at 175 RPM.

Built with custom industrial dust control connections, exclusive WD detachable handle carriage with 5-position pin-set handle lock and 100 ft. 12-3 power cord and 2" x 8" non-marking, ball bearing wheels.

- Powerful 1.25 HP TEFC Dual Capacitor motor. 115V - 230V, 50/60 Hz World Motor
- XHD 11:1 helical-cut, case hardened gears with steel coupler
- 6 Quart, dual-stage vacuum tank with triple filtration
- Includes customer industry skirt for dust pickup
- Exclusive WD(tm) detachable handle carriage design with 5-position pin-set handle lock
- 100 ft, 2-piece SJTOW industrial power cord with molded plug
- Steel brush cover with full wraparound bumper
- 2" x 8" non-marking ball bearing wheels
- Dual steel operating triggers with negative pressure on/off switch
- Comfortable cushion grips
- Optional weights up to 40 lbs.
- 17" and 20" sizes
- Quiet 66 dB operation

Accessories

- **Pad Driver #A0010 (17") #A0011 (20")**
- **Economy Sandpaper Driver #A0014 (17"), #A0014-1 (20")**
- **Professional Sandpaper Driver #A0014-HD (17") #A0014-1HD (20")**
- **Weight Kit #HPA0032-410BLK (17" & 20")**
- **Vacuum Kit #TH01011-GLD (17" & 20")**, Includes 5 quart dual stage vacuum, dust skirt and 1.5" hoses.

17" & 20" Models

Specifications				
Model	Sanding Star 17"	Sanding Star 17" w/ Vacuum	Sanding Star 20"	Sanding Star 20" w/ Vacuum
Part #	#F95-17-01	#F95-17-01S_20	#F95-17SP	F0091-20XHD
Machine Size	17"	17"	20"	20"
Pad Size	16"	19"	16"	19"
Rotary Brush Size	15"	18"	14"	18"
Pad Speed	175 RPM	175 RPM	165 RPM	165 RPM
Gear Box	10:1	10:1	10:1	11:1
Amp Draw	6.7 Amp	6.9 Amp	7.1 Amp	7.3 Amp
All Glide and Glide XHD Sizes				
Motor	1.5 HP, 66 frame dual capacitor powder-coated AC motor (Glide) or chrome AC motor (XHD)			
Power	115V, 60 Hz power, (230V optional)			
Power Cord	50 ft., (14-3) STO power cord with molded plug			

(Specifications subject to change without notice)



**Green Cleaning Approved. Reduces chemicals, water, energy and labor.,
Helps replenish the Earth with Clean Responsibility**