



Dry Floors, Circulate & Exhaust Air

Hawk Industrial Air Mover with 1/2 HP, 3-speed industrial motor will move air consistently to 2950 CFM. Built with super-tough polypropylene housing for long-term use in the toughest of applications; construction, manufacturing and housekeeping applications. Metal cage and safety discharge guard.

Power

- 1/2 HP, 3-speed motor
- 115V, 50/60 Hz power. 230V available.
- 25 ft. 16-3 SJTOW power cord with molded plug
- Top mounted, quick change 3-speed switch

Engineering Design

- Three air flow speeds - 2000 CFM, 2500 CFM and 2950 CFM with switch on housing
- Continuous-duty rugged ball bearing motor
- Polyethylene housing with extended warranty
- Steel fan cage
- Steel handle and air discharge guard
- 8 rubber feet for non-slip positioning
- Stack up to 5 units for easy storage
- Convenient size - 19.5" x 14.5" x 18.25"
- Available in 2 colors; royal blue, and black. Special colors with 25 piece order.

Safety Features

- UL Listed
- Quiet operation with dB levels: Low 59, Medium 62, High 64. Meets GS42 standard.



HAWK Industrial
2950 CFM Air Mover



Specifications

Model#	BH001-3S		
Part #	BH001-BLK, BH001-RYB		
Motor	1/2 HP, 3-speed motor		
Power	115V, 50/60 Hz power		
Motor CFM	2000 CFM	2500 CFM	2950 CFM
Amp Draw	4.3 Amp	4.5 Amp	5.3 Amp
Power Cord	25 ft. 16-3 SJTOW power cord w/molded plug		
Housing	Polyethylene housing		
Positions	0, 45 and 90 degrees		
dB Rating	59 dB (low speed), 62 dB (medium), 64 dB (high). Meets GS42 standard.		
Size	19.5" x 14.5" x 18.25"		
Weight	31 lbs.		

Subject to Change Without Notice



Frame in Royal Blue and Black



Metal Carrying Handle



3-Speed Switch