



Stripping, Scrubbing, Resurfacing



The HAWK Pro is designed for the floor care professional. This severe-duty machine handles the range of tasks with the 180-frame TEFC motor with hardened steel gears that drive scrapers, sanders and tools at 165 RPM. Power to drive sandpaper drivers, diamond pad drivers, Claw, Scraper, and Orbitec tools.

The HAWK Pro includes two removable 25 lb. weights mounted on the brush cover, a convenient upper handle lock, 3" wider handle, a no-spill solution tank, pad driver, and splash guard.

Power

- 1.5 HP, 180 frame, TEFC AC motor
- 115-230 V, 60 Hz (50 Hz optional)
- 50 ft., (12-3) 2 piece industrial power cord with twist lock

Drive System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler. Gears drive brushes and tools at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- Heavy-duty motor guard protects the motor from impact damage
- One piece chrome, heavy duty steel handle with variable position lock
- Ergonomic upper grip handle is 3" wider than standard for leverage. Comfortable vinyl-dipped foam grips
- 17" and 20" steel brush covers with full wraparound bumpers
- Dual steel operating triggers. Thumb operated safety switch
- Negative pressure on/off switch
- 1" x 5" non-marking ball bearing wheels
- Includes diamond driver, 4 gallon solution tank and splash guard
- Includes (2) 25 lb. weight set with mounting lock pins. Added weights give extra down pressure for faster results
- Optional dust pickup system (#HP0031-DC17-BRUTEKIT, #HP0031-DC20-BRUTEKIT)

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

	PRO-17	PRO-20
Model	PRO-17	PRO-20
Item #	F37-03 PRO	F040-03 PRO
Pad Size	16"	19"
Pad Speed	165 RPM	165 RPM
Amp Draw	7.9	8.4
Weight	128 lbs.	130 lbs.
All Sizes		
Motor	1.5 HP, 180 frame, TEFC dual capacitor AC	
Power	115-230V, 60 Hz power (50 Hz optional)	
Power Cord	50 ft., (12-3) 2 piece industrial with twist lock	
Drive Gears	Triple-planetary XHD 11:1 helical-cut industrial	
Sound Level (ave.)	66 dB - Meets GS42 standard	



The Handle-Mounted Hose Support Carries 1.5" and 2" Vacuum



Includes Diamond Pad Driver



Two-Piece Twist Lock Power Cord



Upper Handle Lock is Easy to Access