

HAWK High-Speed Burnisher w/ AC Motor



The Hawk High-Speed Burnisher with AC motor is a balanced force of polishing power. These models are built with a durable 1.5 HP, 56 frame TEFC motor that requires little maintenance, use less power than DC motors, are less effected by heavy hands in operation and runs cleaner than traditional DC motor. The motor shroud protects the inner workings from dust and moisture.

AC motors are often the better choice for use in buildings with older circuitry and with less experienced users. AC motors use less energy than DC and are not as effected by heavy hands in operation, preventing trips on the circuit breakers. AC burnishers spinning at 1250 RPM are equivalent to a DC motors classified as 1500 RPM when its pad is in contact with the floor. Unlike DC motors, AC motor machine do not slow with added burnisher load.

The AC model is the perfect addition to any Green Cleaning program.

Power

- 1.5 HP, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft., (14-3) 2-piece commercial power cord with cord lock
- Multi V-Belt drives pads at 1000 RPM

Engineering Design

- 13", 15", 17" and 20" standard models are built with powder-coated steel brush cover with full wraparound bumper
- 17" and 20" Dust Control models add a dust ring and filter Welded steel frame
- One-piece chrome handle with variable position positive handle lock
- · Comfortable vinyl-dipped foam handle grips
- Thumb-operated safety switch. Negative pressure on/off switch
- Dual steel operating triggers
- 1" x 5" non-marking wheels
- Includes flexible pad holder with pad centering clamp

Safety Features

- Quiet operation 58 dB (Standard), 53 dB (Dust Control). Meets GS42 standard.
- Built with UL listed components

Specifications13"15"17"17"20"20"StandardStandardW/Dust ControlStandardW/Dust ControlPad Size13"15"11"16"20"19"ModelHigh Speed Tow W/AC MotorItem # Amp DrawF1000-13TE 10.0F1000-15TE 11.2F1000-17TE 12.4F1000-20TE D 13.6F1000-20TEDC 13.5Motor1.5 HP, 56 run 15.5 HP, 56 run 15.5 HP, 56 run 50 ft. (14-3) 2000 run 15.5 HP, 56 run <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>								
No. No. <th></th> <th></th> <th></th> <th colspan="4">Specifications</th>				Specifications				
Model High Speed 1000 w/AC Motor Item # F1000-13TE F1000-15TE F1000-17TE F1000-20TE F1000-17TE F1000-20TEDC Amp Draw 10.0 11.2 12.4 11.6 13.5 12.4 Motor 1.5 HP, 56 frame TEFC AC motor Fower Cord 50 ft., (14-3) 2-piece commercial w/ cord lock Fower Cord lock Sound Level (ave.) 58 dB 58 dB 58 dB 58 dB 53 dB 53 dB								
Item # F1000-13TE F1000-15TE F1000-17TE F1000-20TE F1000-17TE F1000-17TE F1000-17TE F1000-17TE F1000-20TEDC 12.4 Amp Draw 10.0 11.2 12.4 11.6 13.5 12.4 Motor 1.5 HP, 56 frame TEFC AC motor F1000-17TE F1000-17TE F1000-20TEDC Power 1.5 HP, 56 frame TEFC AC motor F1000-17TE F1000-17TE F1000-20TEDC Power Cord 50 ft., (14-3) 2-piece commercial w/ cord lock F1000-17TE F1000-20TEDC Belt Drive Multi-V Belt Drive S3 dB 58 dB 53 dB 53 dB 53 dB	Pad Size	13"	15"	17"	16"	20"	19"	
Amp Draw 10.0 11.2 12.4 11.6 13.5 12.4 All Models Motor 1.5 HP, 56 frame TEFC AC motor Power 115V, 50/60 Hz power. 230V available. Vertical available. Power Cord 50 ft., (14-3) 2-piece commercial w/ cord lock Vertical available. Belt Drive Multi-V Belt Drive 58 dB 58 dB 58 dB 53 dB	Model	High Speed 1000 w/AC Motor						
Motor 1.5 HP, 56 frame TEFC AC motor Power 115V, 50/60 Hz power. 230V available. Power Cord 50 ft., (14-3) 2-piece commercial w/ cord lock Belt Drive Multi-V Belt Drive Sound Level (ave.) 58 dB 58 dB 58 dB 58 dB 53 dB	Item #	F1000-13TE	F1000-15TE	F1000-17TE	F1000-20TE	F1000-17TE	F1000-20TEDC	
Motor 1.5 HP, 56 frame TEFC AC motor Power 115V, 50/60 Hz power. 230V available. Power Cord 50 ft., (14-3) 2-piece commercial w/ cord lock Belt Drive Multi-V Belt Drive Sound Level (ave.) 58 dB 58 dB 53 dB 58 dB 53 dB	Amp Draw	10.0	11.2	12.4	11.6	13.5	12.4	
Power 115V, 50/60 Hz power. 230V available. Power Cord 50 ft., (14-3) 2-piece commercial w/ cord lock Belt Drive Multi-V Belt Drive Sound Level (ave.) 58 dB 58 dB 53 dB 58 dB 53 dB	All Models							
Power Cord 50 ft., (14-3) 2-piece commercial w/ cord lock Belt Drive Multi-V Belt Drive Sound Level (ave.) 58 dB 58 dB 53 dB 58 dB 53 dB	Motor		1.5 HP, 56 frame TEFC AC motor					
Belt Drive Multi-V Belt Drive Sound Level (ave.) 58 dB 58 dB 53 dB 58 dB 53 dB	Power		115V, 50/60 Hz power. 230V available.					
Sound Level (ave.) 58 dB 58 dB 58 dB 53 dB 58 dB 53 dB	Power Cord		50 ft., (14-3) 2-piece commercial w/ cord lock					
	Belt Drive		Multi-V Belt Drive					
Machine Weight 84 lbs. 86 lbs. 88 lbs. 88 lbs. 90 lbs. 90 lbs.	Sound Level (ave.)	58 dB	58 dB	58 dB	53 dB	58 dB	53dB	
	Machine Weight	84 lbs.	86 lbs.	88 lbs.	88 lbs.	90 lbs.	90 lbs.	

Subject to Change Without Notice

HAWK ENTERPRISES



Printed USA 11/2020 2902 Park Six Court, Elkhart, IN 46514 www.hawkenterprises.com (574) 294-1910