



Dry Floors, Circulate & Exhaust Air

The HAWK Industrial Air Mover with 1/2 HP, 3-speed industrial motor moves air up to 2950 CFM. Built with super-tough polypropylene housing for long-term use in construction, manufacturing and housekeeping. Built with metal cage and safety discharge.

Power

- 0.5 HP, 3 - speed motor
- 115 V, 50/60 HZ power (230V available)
- 35 ft., (16-3) 2-piece commercial with cord lock
- Top mounted quick change 3-speed switch

Engineered Design

- Three air flow speeds - 2000 , 2500 and 2950 CFM. Moves air up to 60 ft. at high speed
- Speed switch conveniently located next to lifting handle
- Continuous-duty rugged ball bearing motor
- Roto-molded polyethylene housing with lifetime warranty
- Plastic fan wheel
- Steel handle and discharge guard
- 8 rubber feet for non-slip positioning
- Stackable for easy storage
- Convenient size - 19.5" x 14.5" x 18.25"

Safety features

- Quiet operation with dB sound levels: 59 dB (Low Speed), 62 dB (Medium Speed) and 64 dB (High Speed).
- UL Listed



Moves Air at 3 Angles



Specifications

Model	HAWK Industrial Air Mover		
Item #	BH001-02 (Black Housing), BH001-08 (Blue Housing)		
Motor	0.5 HP, 3-speed 110V motor		
Motor CFM	2950 CFM	2500 CFM	2000 CFM
Power Cord	35 ft., (16-3) 2-piece commercial with cord lock		
Auxiliary Outlet	12 Amp with circuit breaker		
Housing	Roto-molded machine housing		
Air Direction	0, 45 and 90 degrees		
Machine Size	19.5" x 14.5" x 18.25"		
Ship Size	20" x 20" x 20"		
Weight	31 lbs.		
Amp Draw	5.3	4.5	4.3
Sound Levels	64 dB	62 dB	59 dB

Subject to Change Without Notice



Moves Air Up to
60 ft. at High Speed



Compact Power
19.5" x 14.5" x 18.25"



Metal Carrying Handle