



Counter Tops, Stairs, Small Spaces

The performance, versatility and value of the HAWK Mighty continues with the new Mighty Mini 10. The 1.0 HP TEFC (Totally Enclosed Fan cooled) AC motor drives 10" rotary brush with risers or 9" pads with pad driver. Ample power in a small and manageable machine. Excellent balance with low center of gravity. Ideal for use in tight spaces, restrooms, edging and stairs.

The innovative design of HAWK Mighty machines incorporates a state of the art "World Motor". Works around the globe without modification.

Power

- 1.0 HP, TEFC AC motor
- 115-230V, 50/60 Hz power
- 50 ft., (14-3) 2-piece commercial power cord with cord lock for rigid handle models

Engineering

- Triple-planetary severe-duty 11:1 helical-cut industrial gears, case hardened with steel coupler
- Gears drive brushes and pads at 165 RPM
- All steel construction with welded, powder-coated frame
- 3 steel handle options - standard 48", short 24" and telescoping 36" - 48". All with 6-position pin lock
- Comfortable vinyl dipped foam handle grips
- Thumb-operated safety switch. Negative pressure on/off switch
- Dual steel operating triggers.
- 1" x 5" non-marking ball bearing wheels
- Optional dust collection kit
- Optional handle mounted cord wrap (#KIT3009-1BLK)

Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components



Mighty Mini 10
w/ 48" Handle

Mighty Mini 10-24
w/ 24" Handle

Mighty Mini 10-TH
w/ Telescoping Handle



Specifications

Model	Mighty Mini 10	Mighty Mini 10-TH	Mighty Mini 10-24
Item #	F60-10	F60-10TH	F60-10-24
Pad Driver Size	9"	9"	9"
Brush with Riser	10"	10"	10"
Handle	48"	36" - 48"	24" 1-piece
	Rigid/Short	Telescoping	Rigid / Short
Speed	165 RPM	165 RPM	165 RPM
Draw	5.9 Amp	5.9 Amp	5.9 Amp
Weight	71 lbs.	70 lbs.	69 lbs.

All Models

Motor	1.0 HP, 56 frame, dual capacitor AC motor
Power Source	115-230V, 50/60 Hz power
Power Cord	50 ft., (14-3) 2-piece commercial with cord lock
Driver System	Triple-planetary XHD 11:1 helical-cut industrial gears
Sound Level (ave.)	64 dB - Meets GS 42 Standard


Subject to Change Without Notice



Works in
Tight Spaces



Low Rise Profile - Easy
Working Under Sinks
and Partitions



Handle with 6-Position
Pin Lock



Telescoping Handle
Adjusts from 36" to 48"