



### Stripping, Scrubbing, Polishing

Machine operators will appreciate the performance, versatility and value in the HAWH Mighty. The 1.0 HP TEFC (Totally Enclosed Fan Cooled) AC motor and XHD gears deliver huge power in a small and manageable machine. The Mighty is ideal for use in tight spaces, restrooms, edging and stairs.

The HAWK Mighty innovative design incorporates a state of the art "World Motor" works around the globe without modification .

#### Power

- 1.0 HP, TEFC AC Motor
- 115-230V, 50/60 Hz power
- 50 ft., (14-3) 2-piece commercial power cord with cord lock

#### Drive System

- Triple-planetary severe-duty 11:1 helical-cut industrial gears, case hardened with steel coupler
- Gears drive brushes and pads at 165 RPM

#### Engineered Design

- All steel construction with welded, powder-coated frame
- Telescoping handle (TH models) adjusts from 36" to 48"
- Brush covers have full wraparound bumper
- One piece powder-coated, heavy-duty steel handle with 6-position pin lock
- Comfortable vinyl dipped foam handle grips
- Thumb-operated safety switch. Negative pressure on/off switch
- Dual steel operating triggers
- 1" x 5" non-marking ball bearing wheels
- Optional dust collection kit
- Optional handle mounted cord wrap (#KIT3009-1BLK)
- Optional 4 gallon solution tank (#A0001-Color4)

#### Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components



### Specifications

Model	MIGHTY 13	MIGHTY 13-TH	MIGHTY 15	MIGHTY 15-TH
Item #	F60-13	F60-13TH	F60-15	F60-15TH
Handle	Rigid	Telescoping	Rigid	Telescoping
Size	13"	13"	15"	15"
Pad Size	12"	12"	14"	14"
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	4.9	4.9	6	6
Weight	87 lbs.	87 lbs.	88 lbs.	88 lbs.

### All Models

Motor	1.0 HP, TEFC AC
Power Source	115-230V, 50/60 Hz
Power Cord	50 ft., (14-3) 2-piece commercial with cord lock
Gear Box	Triple-planetary XHD 11:1 helical-cut industrial
Sound Level (ave.)	64 dB - Meets GS42 standard


Subject to Change Without Notice



Works in Tight Spaces



Telescoping Handle Adjusts from 36" to 48"



Optional 2.5-Gallon Solution Tank



Handle with 6-Position Pin Lock