



Stripping, Scrubbing, Carpet Maintenance



Optional Cord Wrap

The HAWK Glide delivers up to twice the performance of traditional floor machines with greater safety and 1/3 less amp draw. The unique "Floating Head" WD™ Wheels Down handle carriage design provides 100% contact with the floor and steers the Glide in forward and backward movement - unlike the side-to-side movements of swing buffers. Use the Glide XHD model for the toughest jobs with 11:1 industrial gears to power tools and drivers at 165 RPM. Easy to learn. Easy to use.

Power

- 1.5 HP, dual capacitor AC Motor
- 115-230V, 60 Hz (50 Hz optional)
- 50 ft., (14-3) 2-piece commercial power cord w/ cord lock
- **Glide** uses 10:1 helical-cut commercial gears to drives brushes, pads and tools at 175 RPM
- **Glide XHD** (Extra Heavy Duty) uses triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler drives brushes, pads and tools at 165 RPM

Engineered Design

- Exclusive "Floating Head" wheels down detachable handle carriage design produces 100% flat contact with the floor
- All steel construction with welded frame. Heavy-duty powder-coated steel handle with 4-position pin lock
- 17" and 20" steel brush covers with full wraparound bumper
- Dual steel operating triggers. Thumb-operated safety switch
- Comfortable vinyl-dipped foam handle grips
- 2" x 6" non-marking ball bearing wheels
- Glide Deluxe model (#F91-17-DX, #F91-20-DX) adds the 4 Gallon solution tank, premium pad driver and splash guard
- Optional splash guard (#SPLASH17-WD, #SPLASH20-WD) and dust collection kit (#HP0031-DC17 #HP0031-DC20)
- Optional 4 gallon solution tank (#A0001-Color4)

Safety Features

- Quiet 66 dB operation. Meets GS42 standard
- Built with UL listed components



Specifications

Model	Glide 17	Glide 17XHD	Glide 20	Glide 20XHD
Item #	F91-17-01	F92-17-01	F91-20-01	F92-20-01
Machine Size	17"	17"	20"	20"
Pad Size	16"	16"	19"	19"
Motor Cover	Powder-Coated	Chrome	Powder-Coated	Chrome
Drive Gears	10:1	11:1	10:1	11:1
Pad Speed	175 RPM	165 RPM	175 RPM	165 RPM
Amp Draw	6.7	7.1	6.9	7.3
Weight	113 lbs.	113 lbs.	115 lbs.	115 lbs.
dB Rating	66 dB	69 dB	66 dB	69 dB

All Models

Motor	1.5 HP, 66 frame dual capacitor AC
Power Source	115V, 60Hz power. (230V Optional)
Power Cord	50 ft., 2-piece (14-3) industrial w/ cord lock

Subject to Change Without Notice



Optional 4 Gallon Solution Tank



Optional Dust Control Ring Connects to Tank



Optional Osprey Sprayer Kit



4 Position Pin Lock Handle w/ All Steel Construction