



## Stripping, Scrubbing, Carpet Maintenance

The HAWK Glide 2-Speed machines deliver up to twice the performance of traditional floor machines. The unique "Floating Head" WD™ Wheels Down handle carriage design provides 100% contact with the floor and steers the Glide in forward and backward movement - unlike the side-to-side movements of swing-buffers. The 2-speed motor scrubs at 165 RPM (Glide) or 175 RPM (XHD).

### Power

- 1.5 HP, dual capacitor AC motor
- 115V, 50/60 Hz power
- 50 ft., 2-piece (14-3) commercial power cord with cord lock
- Hi/Low speed switch is located on the motor
- **Glide 2-Speed** uses triple-planetary HD 10:1 helical-cut commercial gears to drives brushes and pads at 175 / 320 RPM
- **Glide 2-Speed XHD** (Extra Heavy-Duty) uses triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler. Drives brushes and pads at 165 / 300 RPM

### Engineered Design

- 17" and 20" steel brush covers with full wraparound bumper
- All steel construction with welded frame. Heavy-duty powder-coated detachable steel handle with 4-position pin lock
- Exclusive WD™ Wheels Down handle design
- Dual steel operating triggers. Thumb-operated safety switch
- Comfortable vinyl-dipped foam handle grips
- 2" x 6" non-marking ball bearing wheels
- **Glide 2-Speed Deluxe** models add the 4 gallon solution tank, premium pad driver and splash guard
- Optional splash guard (**#SPLASH17-WD**, **#SPLASH20-WD**) and dust collection kit (**#HP0031-DC17** **#HP0031-DC20**)
- Optional 4 gallon solution tank (**#A0001-Color4**)
- Optional Osprey sprayer kit

### Safety Features

- Quiet 66 dB operation. Meets GS42 standard
- Built with UL approved components



### Specifications

Model	GLIDE 17-2S	GLIDE 17-2SXHD	GLIDE 20-2S	GLIDE 20-2SXHD
Item#	F93-17	F93-17	F94-17	F0091-20
Drive Gears	10:1	11:1	10:1	11:1
Machine Size	17"	17"	20"	20"
Pad Size	16"	16"	19"	19"
Speed RPM	175 / 320	165 / 300	175 / 320	165 / 300
Amp Draw	8.5 / 9.1	8.5 / 9.1	9.2 / 9.6	9.2 / 9.6
Weight	113 lbs.	113 lbs.	115 lbs.	115 lbs.

  

All Models	
Motor	1.5 HP 2-speed rectified DC motor
Power	115V, 50/60 Hz (230V Optional)
Power Cord	50 ft., (14-3) 2-piece commercial w/cord lock
Sound Level	62 dB (low speed) - 69 dB (high speed) - Meets GS42 Std.

Subject to Change Without Notice



Optional 4 Gallon Solution Tank



Optional Dust Control Ring Connects to Tank



Optional Osprey Sprayer Kit



5-Position Pin Lock Handle All Steel Construction