



Dry Floors, Circulate and Exhaust Air

The HAWK BVP50 Air Mover is the safest and most efficient centrifugal air mover on the market. Our 1/2 HP motor moves air at up to 2820 CFM with just 4.5 amp draw.

Control the air flow and amp draw with our state of the art 2-speed moisture resistant switch. The roto-molded body is strong, lightweight and easy to clean, transport and stack. The BVP50H model adds a telescoping handle frame with transport wheels.

Engineered Design

- The 1/2 HP, 2-speed motor is efficient and produces up to 2820 CFM airflow
- 25 ft. 16 AWG power cord
- The motor is sealed to prevent moisture from entering and damaging internal motor components
- The side-mounted 2-speed switch is moisture resistant
- Sturdy roto-molded plastic frame design has a profile that allows for vertical stacking up to 4 units for convenient storage
- The **BVP50** multipurpose design directs air at 3 angles (horizontally, 45° and 90°)
- The **BVP50H** adds a telescoping handle and transport wheels. Use horizontally, or tip back 90 degrees and move air straight upward
- A plastic cage protects motor and fans from debris
- C-ETL listed
- 5 year warranty on roto-molded chassis. 2 year warranty on parts



HAWK BVP50
2820 CFM Air Mover



HAWK BVP50H
with Handle and
Transport Wheels



Specifications

Model	BVP50, BVP50H (w/ Handle & Wheels)
Motor	115V, 1/2 HP, 60Hz
Attached Cord	25 Ft. 16 AWG
Air Flow	2820 CFM (High Speed) / 2390 CFM (Low Speed)
Amp Draw	4.5 Amp (High Speed) / 2.8 Amp (Low Speed)
Static Pressure	2.5" Max
Air Flow Direction	0, 45 and 90 degrees
Frame Construction	Sturdy Roto-Molded Plastic
Stackable	4 units
Weight	25 lbs. (net) / 28 lbs. (gross)
Size (L x W x H)	22.5" x 20" x 13"
Sound Level (ave.)	74 dB
Certification	C-ETL-US

Subject to Change Without Notice




Store Up To
5 Stacked Units



BVP50H Adds Dual
Transport Wheels and
Telescoping Handle



Direct Airflow at 3 Angles
(0°, 45° and 90°).



Compact Air
Moving Power