



Large Area Vacuum Cleaning



Titan 29



Includes:
Wet/Dry Tool Kit
#HPVA002

15' Flexible
Vacuum Hose
#HPTV1060



The HAWK Titan 29 and Titan 55 wet/dry tank vacuums are built for years of trouble-free service. Ideal for large volume recovery of liquids and solid wastes. Safely move heavy loads up to 400 lbs. on large rear wheels and industrial front casters. The corrosion-resistant tank is easy to rinse out through the 13" top entry hole. Drain liquids and debris from the rear-mounted quick-drop drain valve.

Power

- 2 HP, 2-stage heavy-duty bypass motor (230V optional)
- 35 ft., (16-3) 2-piece commercial power cord with cord lock

Engineered Design

- 112 CFM air flow. 117" water lift.
- Corrosion-resistant roto-molded tank is easy to clean
- Quick-drop drain valves - 1.5" (V29) and 3" (V55)
- V29 - Large 8" rear wheels and strong 4" front casters
- V55 - Large 10" rear wheels and strong 5" front casters
- Powder-coated steel handle and carriage
- The automatic liquid shut-off valve prevents motor flooding
- Quick drop drain hose reduces need for lifting
- Includes wet/dry tool kit (#HPVA002)
- Includes 15ft. flexible vacuum hose (#HPTV1060)
- Includes one acid and mildew resistant, non-pleated washable synthetic cloth dust bag (#HPVA4040) and mounting ring (#VA2018)

Safety Features

- Quiet operation - 68 dB. Meets GS42 requirements
- Built with UL / CUL approved components

SPECIFICATIONS

Model	Titan 29	Titan 55
Item #	V29-V	V55-V
Capacity	29 gallon	55 gallon
Wet Pick Up	22 gallons	48 gallons
Dry Pick Up	2 bushel (18.6 gal)	4 bushel (37.2 gal)
Motor	2 HP DC, 2-Stage	2 HP DC, 2-Stage
Power	115V, 50/60 Hz	115V, 50/60 Hz
Amp Draw	10.7 Amp	10.7 Amp
Power Cord	35 ft., (16-3) 2-piece	35 ft., (16-3) 2-piece
Water Lift	117"	117"
Air Flow CFM	112	112
2 Wheels - Rear	8"	10"
2 Casters - Front	4"	5"
Weight	80 lbs	94 lbs
Drain Valve	1.5"	3"
Dimensions (HxDxW)	40" x 33.5" x 20.5"	45" x 38" x 25.5"
Sound Levels (ave.)	68 dB	68 dB


Subject to Change Without Notice



Titan 29
Tank Vacuum



Titan 55
Tank Vacuum



Quick-Drop
Drain Valves
1.5" (V29)
3" (V55)



Wheels, Casters &
Molded Tank are
Mounted on Strong
Steel Frame