

# HAWK HD & XHD 2-Speed Professional Floor Machines



## Stripping, Scrubbing, Carpet Care

The HAWK HD 2-Speed and HAWK XHD 2-Speed floor machines are tough and versatile. Change between low and high speed as the job requires. Powered by a 1.5 HP DC rectified motor.

Choose the HD for standard scrubbing and stripping at 175/320 RPM. The XHD model uses 11:1 helical cut gear set for more challenging work including carpet care and natural stone maintenance. XHD models can bear extra weights for greater down pressure and faster results.

#### Power

- 1.5 HP, DC rectified 2-speed motor
- 115V, 50/60 Hz power (230V optional)
- HD 2-Speed uses triple-planetary 10:1 helical-cut commercial gears. Drives brushes and pads at 175/320 RPM
- HD-2-Speed Cord 50 ft., (14-3) 2-piece commercial with cord lock
- XHD 2-Speed (Extra Heavy Duty) planetary 11:1 helical-cut industrial gears, case hardened with steel coupler. Chrome plated motor cover. 165/300 RPM pad speed
- XHD 2-Speed Cord 50 ft., (12-3) 2-piece industrial with cord lock
- Hi/Low speed switch is conveniently located on switch box handle

### **Engineered Design**

- · All steel construction with welded, powder-coated frame
- One piece, chrome plated heavy-duty steel handle with variable position lock and vinyl-dipped foam grips
- · Powder-coated steel brush covers with full wraparound bumpers
- Dual steel operating triggers. Negative pressure on/off switch
- Thumb-operated safety switch. 1" x 5" non-marking wheels
- · Optional frame weights for XHD only
- Optional DX kit includes solution tank, pad driver & splash guard

#### **Safety Features**

- Quiet 60dB (HD 2-Speed) and 66 dB (XHD 2-Speed) operation.
   Meets GS 42 Standard
- · UL / CUL listed







Easy Transport 1"x5" Non-Marking Wheels



DX Package w/ Solution Tank, Pad Driver & Splash

	Spec	ifications	s HD 2-Speed				Spec	ecifications XHD		
Model	HD-2 Spd13	HD-2 Spd-15	HD-2 Spd-17	HD-2 Spd-20		XHD-2 Spd-13	XHD-2 S	3pd-15	Spd-15 XHD-2 Spd-17	
Item #	F03-13-01	F03-15-01	F03-17-01	F03-20-01		F04-13-01	F04-15-0	1	1 F04-17-01	
Size	13"	15"	17"	20"		13"	15"		17"	
Pad Size	12"	14"	16"	19"		12"	14"		16"	
Amp Draw	7.8 / 8.2	8.1 / 8.5	8.5 / 9.1	9.2 / 9.5		7.8 / 8.2	8.1 / 8.5		8.5 / 9.1	
Weight	87 lbs	91 lbs	94 lbs	97 lbs		87 lbs	91 lbs		94 lbs	
	All HD 2-Speed Models					All XHD 2-Speed Models				
Motor	1.5 HP, DC rectified 2-speed					1.5 HP, DC rectified 2-speed				
Drive Gears	Triple-planetary 10:1 commercial					Triple-planetary XHD 11:1 industrial\				
Pad Speed	175/320 R	PM				165/300 RPM				
<b>Power Source</b>	. , ,					115V, 50/60 Hz (230V optional)				
Power Cord	50 ft., (14-3	3) 2-pc. comm	ercial w/cord lo	ock		50 ft., (12-3) 2-p	c. industrial v	v/c	v/cord lock	
Sound Level	60dB (175)	60dB (175) - 69dB (320)				69dB (165) - 72dB (300)				
	Meets GS4	Meets GS42 standard				Meets GS42 standard				

ELKHART, IN