



**19" Steel Plate
for 17" &
20" Floor
Machine**



**12" Steel Plate
for 13" Floor
Machine**



**Standard Blade
Mount for
Wide Cutting Edge**



**45° Mount for
Sharp Cutting Point**



ELKHART, IN



Specifications

| Model | Scraper 13" | Scraper 17" | Scraper 20" |
|---------------------------|---|-------------|-------------|
| Item # | #HP0034 | #HP0033 | #HPA0035 |
| Floor Machine Size | 13" | 17" | 20" |
| Scraper Plate Size | 12" | 16" | 19" |
| Drive Plate Speed | 165 RPM | 165 RPM | 165 RPM |
| Weight | 27 lbs. | 36 lbs. | 39 lbs. |
| Cutter Blade Size | 1.0" x 1.0" x 1/4" | | |
| Clutch Plate | Aluminum 9200 Style Plate with Custom Milled Design | | |
| Riser | 1.25" Tall Plastic | | |
| Floor Machine Requirement | 1.5 HP Severe-Duty with 11:1 Industrial Gear Set | | |

Subject to Change Without Notice

Scraping, Soil & Coatings Removal

Use the HAWK Scraper to remove tile adhesives, carpet backing, industrial grease & soil, and coatings from hard surfaces. The Scraper drives six 1"x1" carbide steel cutters on a dual-position rigid mount to scrape and scratch surfaces.


Drive the Scraper with a HAWK severe-duty, 175 RPM floor machine with a 1.5 HP motor. Higher speed machines are not recommended.

Engineered Design


- Three sizes; 13", 17" and 20"
- 3/8" thick steel plate construction. The plate is electroplate coating resists corrosion.
- The plate is fit with six (6) tungsten steel cutter head holders, mounted with easily removed allen head screws
- Each cutter head holder carries one (1) 1" x 1" carbide cutting blade. Each blade has 8 cutting edges.
- Mount the blade with a wide cutting edge, or turn 45 degrees to create a sharp cutting point. (See photo at left.)
- The Scraper plate mounts on the floor machine with a custom milled aluminum clutch plate with a riser (included)
- The aluminum clutch plate won't seize onto the drive hub
- Add the optional dust ring and vacuum mounting kits on your HAWK severe-duty floor machine for handling dusty soils
- Add the optional machine weights for greater down pressure and faster scraping results

Safety Tips:

- 17" and 20" Scrapers are built with mounting grip recesses for safer handling and mounting
- Always unplug the floor machine before mounting or removing the Scraper driver
- Always wear gloves when handling sharp cutting edge tools




1" x 1" Blades Mount on the Holder with SS Bolts



17" and 20" Have Built-In Mounting Grip Recess



Carbide Steel Blades (3) per Replacement Kits



Scraper Mounts on Hawk Floor Machine with 9200 Style Clutch Plate